

RZWS

Deliver water across all levels of the root zone for high-efficiency subsurface irrigation of trees and shrubs.

KEY BENEFITS

- Patented StrataRoot™ Baffle System diverts water to all levels of the rootzone while adding strength to the unit
- Durable locking cap for vandal resistance
- Pressure-compensating bubbler for accurate water flow
- Built-in Hunter Swing Joint for direct installation to ½" PVC fitting
- Preassembled for fast installation

OPERATING SPECIFICATIONS

- Bubbler flow rates: 0.25 or 0.50 GPM
- Recommended pressure range: 15 to 70 PSI
- Warranty period: 2 years

FACTORY-INSTALLED OPTIONS

- Check valve (HCV)
- Locking reclaimed water purple cap

USER-INSTALLED OPTIONS

- Fabric sleeve to prevent soil intrusion in sandy areas for 18" and 36" models (P/N RZWS-SLEEVE)
- Replacement cap for 18" and 36" models (P/N 913300SP)
- Locking reclaimed purple cap for 18" and 36" models (P/N 913301SP)
- Reclaimed water purple cap for 10" model (P/N RZWS10-RCC)



RZWS-10

Tube diameter: 2"
Cap diameter: 3"
Length: 10"

RZWS-18

Tube diameter: 3"
Cap diameter: 4¾"
Length: 18"

RZWS-36

Tube diameter: 3"
Cap diameter: 4¾"
Length: 36"



**Reclaimed models available
(Add -R to model number)**

ROOT ZONE WATERING SYSTEM - SPECIFICATION BUILDER: Order 1 + 2 + 3

1	Model	2	Bubbler Flow Rate	3	Options
	RZWS-10 = 10" Root Zone Watering System	25 = 0.25 GPM		(blank) = No option	
	RZWS-18 = 18" Root Zone Watering System	50 = 0.50 GPM		CV = Check valve	
	RZWS-36 = 36" Root Zone Watering System	(blank) = No bubbler or swing joint		R = Reclaimed cap	
				CV-R = Check valve with reclaimed cap	

Examples:

RZWS-10-50-CV = 10" Root Zone Watering System at 0.50 GPM, with check valve
RZWS-36-25-CV-R = 36" Root Zone Watering System at 0.25 GPM, with check valve and reclaimed cap

ADDITIONAL OPTION (SPECIFY SEPARATELY)

RZWS-SLEEVE = Field-installed sleeve made from filter fabric